

CERTIFICATE

of constancy of performance

1922 - CPR - 1586

In compliance with Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation or CPR), this certificate applies to the construction product

LMK Post Tensioning System with 2 to 37 strands for internal and external prestressing of structures with bonded and unbonded strands

(For list of controlled characteristics of the product see Annex I to 1922-CPR-1586 that is an inseparable part of this certificate)

placed on the market under the name or trade mark of

HiSCS S.M.S.A - Highway Special Construction Systems 16, Kifissias Ave., PC 11526 Athens, Greece

and produced in the manufacturing plant

Liuzhou Jinxin Technology Co. Ltd.

No.1 Industrial Park, Liujiang District, Liuzhou City, Guangxi, China New planning area, First Industrial Park, LiuDong New District Liuzhou. Guangxi Province, China

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in the

ETA-20/0837, issued on 17.11.2020 and

EAD 160004-00-0301

under system 1+ for the performance set out in this certificate are applied and that the factory production control conducted by the manufacturer is assessed to ensure the constancy of performance of the construction product.

This certificate was first issued on 23.07.2021 and will remain valid as long as neither the ETA, the EAD, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified factory production control certification body. The certificate is supported through surveillance audits. The validity of the certificate may be confirmed in the CE register at the web address www.dedal-bg.net.







dipl. eng. Anna Vasileva

Burgas, 22 October 2025

Ref. No. 04-00



ANNEX I TO CERTIFICATE OF CONSTANCY OF PERFORMANCE 1922-CPR-1586/ 22.10.2025 (page 1/1)

LMK Post Tensioning System with 2 to 37 strands (Bearing plate, Anchor head, Wedge), for internal and external prestressing of structures with bonded and unbonded strands with controlled characterisitics, acc. to EAD 160004-00-0301:

- Resistance to static load, clause 2.2.1;
- Resistance to fatigue, clause 2.2.2;
- Load transfer to the structure, clause 2.2.3;
- Friction coefficient, clause 2.2.4;
- Deviation, deflection(limits) for internal bonded tendon, clause 2.2.5;
- Corrosion protection, clause 2.2.13;
- Reaction to fire, clause 2.2.35;
- Content, emission and/or release of dangerous substances, clause 2.2.36.









Manager:

dipl. eng. Anna Vasileva

Issued: Burgas, 22 October 2025 Ref. No. 04-00